



“DFWLID” Stainless Steel Weight Indicator With Large Digits LCD Display



Easy to program and use, versatile and high performing weight indicator. The 40mm big coloured backlit display gives a clear view of the weight and helps the user during the weighing operations. The wide range of available functions and interfaces make it suitable for multiple industrial and commercial weighing applications, such as floor scales, mobile weighing, etc. Fitted with and IP68 stainless steel case and a built in rechargeable battery. CE-M approvable (OIML R-76/EN 45501)

MAIN FEATURES



- 5-key functional waterproof keypad
- Backlit 40mm LCD display with 6 high contrast digits with icons for showing the active functions.
- Colour and brightness of the backlighting customizable from Setup.
- Easy to clean stainless steel IP68 case, resistant to harsh and corrosive environments.
- Dimensions: 243 x 145 x 78.4mm.
- Suitable for use on the table, column or wall.
- A/D 24 bit, 4 channel convertor, max. 200 conv./sec. Autoselect and up to 8 signal linearisation points.
- Up to 10,000e or multirange 3 x 3000e @ 0.3 microV/d in CE-M approved versions for legal for trade use.
- Up to 1,000,000 displayable divisions with internal resolution up to 3,000,000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Power supply through built-in rechargeable battery, with 40 operating time and fitted with external battery charger.

Operating Modes: High Resolution x 10, Net/Gross or lb/kg conversion, Accumulation, Formula weighing, +/- Checkweighing, Percentage Weighing, Approved transmission of weight to PC/PLC with Alibi Memory option, Counting, In/Out Truck Weighing, Hold and Peak.